Washware Essentials
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.washwareessentials.co.uk
Email: enquiries@washwareessentials.co.uk

Foot Pedal Bottle Fillers (Non-Chilled)



Product Code: DFWHCF-PEDAL

Foot Pedal Bottle Filling Fountains

Product Code DFWHCF-PEDAL

Stainless steel foot pedal operated bottle filling fountains. No touch operation has become very important in the fight to prevent cross contamination and in the fight to prevent the spread of viruses and germs. The stainless steel bottle filling fountain has a no touch (by hands) operation with a WRAS approved foot valve. The foot valve has a water saving on / off operation preventing the water running on when the foot valve is released. The foot operated valve can either be wall mounted or floor mounted by simply turning the foot lever around. The swan neck bottle filling tap is WRAS approved and has no button for true hands free operation of the bottle filling fountain. In today's climate no touch bottle filling fountains offer a safe source of drinking water whilst reducing the risk of cross contamination from users all touching the same surface.

- Foot pedal operated stainless steel bottle filling fountain.
- **WRAS approved foot valve.**
- **WRAS approved swan neck bottle filling tap.**
- Bottle filling tap with adjustable water flow control.
- 1.6mm thick grade 304 stainless steel for extra vandal resistance and durability.
- Radius front design for protection of users.
- Supplied with wall bracket and 32mm flush grated waste fitting.
- Our products are often copied, please beware of cheap imported drinking fountains with low quality stainless steel, and non WRAS approved valves, make sure you get the WRAS approval number and the valves have the correct markings to comply with the WRAS approval.
- Please ensure that products fitted outside are drained down and isolated in cold weather to avoid damage to the valve and bottle filler.
- Foot operated drinking fountains with drinking water taps are also available.
- To ensure the proper functioning and longevity of this unit, a Y-strainer or filter must be installed as part of the water supply system. The Y-strainer / filter is essential for protecting the internal components and maintaining the correct flow characteristics of the tap. Failure to install a Y-strainer or filter will result in the warranty being void.

Size

- 305mm wide.
- 350mm front to back.
- 150mm high plus 75mm splash back.

Delivery

- From stock usually 1 to 2 working days.

Options

- 32mm plastic bottle trap.
- 32mm chrome plated brass bottle trap with chrome brass pipe and wall flange.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**