Washware Essentials
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.washwareessentials.co.uk
Email: enquiries@washwareessentials.co.uk

Hand Wash Troughs With Knee Operated Taps





Product Code: WTA-KV

Stainless Steel Hand Washing Trough with Knee Operated Taps – 442mm Projection

Product Code WTA-KV

The WTA-KV stainless steel wash trough provides a practical hands-free handwashing solution, supplied complete with knee-operated time-flow valves and fixed chrome-plated basin spouts. Operating the water by knee reduces the need to touch the taps by hand, making the trough particularly suitable for workplaces, food preparation areas, healthcare support areas, workshops and other environments where hand hygiene is important.

Manufactured in one piece from 1.2mm thick stainless steel, the WTA-KV is available in four standard lengths for 2–4 users. Each washing position is supplied with a chrome-plated knee valve and fixed deck-mounted spout, providing a complete multi-user handwashing solution ready for connection to the site water supply.

Key Features

- Stainless steel communal hand washing trough with knee-operated controls.
- Manufactured in one piece from 1.2mm thick stainless steel.
- Hands-free water operation helps reduce hand contact with tap controls.
- Supplied with chrome-plated knee-operated time-flow valves.
- Supplied with chrome-plated fixed deck-mounted basin spouts.
- Time-flow valves operate for approximately 15 seconds at 3 bar water pressure.
- Knee valves supplied with 15mm compression connections.
- Four standard lengths for 2,3 and 4 users.
- 442mm projection from the wall.
- Integral wall-fixing brackets.
- Suitable for wall-mounted installation with optional front support legs.
- Standard sizes held in stock for fast UK delivery.

Sizes & Number of Users

- 1200mm – 2 users
- 1500mm – 3 users
- 1800mm – 3 users
- 2400mm – 4 users

Projection: 400mm front to back
Rear upstand: 39mm

Each user position is supplied with its own knee-operated time-flow valve and fixed basin spout.

Knee Operated Time-Flow Valves

The WTA-KV uses knee-operated valves to control the water without the user needing to operate the tap by hand.

Pressing the knee control starts the water flow, which then automatically shuts off after approximately 15 seconds at 3 bar water pressure. This helps reduce unnecessary water use while allowing the user to wash their hands without touching conventional tap handles or controls.

The chrome-plated knee valves are supplied with 15mm compression connections.

Basin Spouts & Water Supply

Each handwashing position is supplied with a fixed chrome-plated deck-mounted basin spout.

The knee valve controls the water supply to the corresponding spout. Interconnecting pipework between the valves and spouts is not supplied and should be provided by the installer to suit the individual installation.

Where temperature-controlled warm water is required, a suitable thermostatic mixing valve can be incorporated into the water supply. TMV3 mixing valves are available as an optional extra.

Hands-Free Handwashing

Knee operation is particularly useful where reducing hand contact with washroom fittings is desirable.

Unlike conventional taps, the user does not need to touch a handle, button or lever with freshly washed hands to stop the water. The timed shut-off also means the water automatically stops after use.

This makes the WTA-KV particularly suitable for applications such as:

- Food preparation and food processing areas.
- Commercial kitchens and catering environments.
- Workshops and industrial workplaces.
- Healthcare and clinical support areas.
- Laboratories and technical work areas.
- Commercial and staff handwashing facilities.

Delivery

In stock – usually delivered within 1–2 working days.

Standard WTA-KV wash troughs are held in stock for fast UK delivery.

Optional Extras

- Stainless steel front support legs.
- TMV3 thermostatic mixing valves.
- 38mm plastic bottle trap.
- Chrome-plated brass bottle trap with chrome waste pipe and flange.
- Stainless steel bottle trap cover.
- Stainless steel wall-mounted and deck-mounted soap dispensers.
- Stainless steel paper towel dispensers.

Cleaning & Maintenance

Clean the stainless steel trough regularly using warm soapy water or a mild detergent. Avoid bleach, chloride-based cleaners, steel wool and other aggressive or abrasive cleaning products that may cause staining or damage to the stainless steel surface.

Chrome-plated valves and spouts should be cleaned with a mild non-abrasive cleaner and soft cloth to protect the plated finish.

For full stainless steel care instructions, see our Stainless Steel Cleaning Guide.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**