




Pillar Laboratory Tap



Product Code: ARB-PLBTAP

Pillar Laboratory Tap

Product Code ARB-PLBTAP

- Pillar laboratory tap with removable nozzle.
- WRAS Approved.
- Pillar laboratory tap for all applications where a header tank supply is present.
- Full-bore nozzles are available on request.
- All brass body, coated in Rilsan plastic.
- Body colour is Ral 9016 white.
- Green handle.
- Chemical resistant plastic ABS handwheel.

Connection and Mounting

- 1/2" BSP male flat ended shank x 60mm long with back nut.
- Comes as standard with an anti-rotation base with location pin.
- 2 x holes required 1 x 22mm tap hole and 1 x 5mm for the anti-rotation pin, a template is supplied with the tap.

Pressures

- Maximum pressure: 100PSI (Recommended 20PSI).
- Flow rate: 20PSI = 12 Litre/min.

Delivery

- From stock usually 3 to 5 working days.

All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement. All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.