Washware Essentials
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.washwareessentials.co.uk
Email: enquiries@washwareessentials.co.uk

Stainless Steel Junior Wash Trough 370mm Projection



Product Code: WT-370

Stainless Steel Junior Hand Washing Trough – 370mm Projection

Product Code WT-370

The WT-370 stainless steel wash trough combines a reduced 370mm projection with a robust communal handwashing design, making it particularly suitable for schools, junior washrooms and other installations where a more compact trough is required. Available in three standard lengths for 3–4 users, its reduced front-to-back dimension provides easier access for younger users while taking up less washroom floor space.

Manufactured in one piece from 1.2mm thick Grade 304 stainless steel, the WT-370 is supplied with a central 38mm waste fitting and integral wall-fixing brackets. Tap holes are drilled to your specification, allowing the trough to accommodate different tap types and water supply arrangements. All three standard sizes are held in stock for fast UK delivery.

Key Features

- Manufactured in one piece from 1.2mm thick Grade 304 stainless steel.
- Compact 370mm projection from the wall.
- Three standard lengths for 3–4 users.
- Tap holes drilled to customer specification.
- Supplied with central 38mm waste fitting.
- Integral wall-fixing brackets.
- Suitable for wall-mounted installation with optional front support legs.
- Reduced projection makes the trough particularly suitable for junior and school washrooms.
- Standard sizes held in stock for fast UK delivery.
- Manufactured in accordance with BS EN 14296:2015+A1:2018.

Sizes & Number of Users

- 1500mm – 3 users
- 1800mm – 3 users
- 2400mm – 4 users

Projection: 370mm front to back
Bowl depth: 150mm
Rear upstand: 25mm

The reduced 370mm projection provides a more compact alternative to our standard 400mm projection wash troughs, making the WT-370 particularly useful where easier reach or reduced projection into the washroom is required.

Tap Hole Options

The WT-370 wash trough is drilled to suit your chosen tap configuration. Please select the required option when ordering.

Available standard options include:

- One pair of 22mm tap holes per user for separate hot and cold taps.

- Single 22mm tap hole per user for cold or pre-mixed water taps.
- Single 35mm tap hole per user for monobloc mixer taps.
- Special tap-hole requirements can be accommodated – select Special Requirements and we will contact you to confirm the specification.

For a wider choice of lengths from 500mm to 2400mm with the same flexibility to specify your tap holes, see our WTN Stainless Steel Wash Trough.

For nursery and early-years installations requiring an even shorter projection and flexible user spacing, see our NWT Nursery Wash Trough.

Delivery

In stock – usually delivered within 1–2 working days.

All three standard WT-370 sizes are held in stock for fast UK delivery.

Optional Extras

- Commercial taps including time-flow, sensor and mixer options.
- 600mm junior-height stainless steel front support legs.
- 950mm standard-height stainless steel front support legs.
- 38mm plastic bottle trap.
- Chrome-plated brass bottle trap with chrome waste pipe and flange.
- Stainless steel bottle trap cover.
- Stainless steel wall-mounted and deck-mounted soap dispensers.
- Stainless steel paper towel dispensers.

DfE & BS EN 14296 Compliance

The WT-370 wash trough is manufactured in accordance with BS EN 14296:2015+A1:2018 – Sanitary appliances – Communal washing troughs and is suitable for installation in schools, colleges and other educational facilities.

The trough is designed to form part of a Department for Education (DfE) compliant washroom installation, incorporating an integral rear upstand and allowing for contractor-supplied wall finishes, splashbacks, concealed services and access panels where required by the project specification.

The installation height should be selected to suit the intended age group and project requirements. Overall compliance with the Department for Education School Output Specification is achieved through the completed washroom installation.

Cleaning & Maintenance

Clean stainless steel regularly using warm soapy water or a mild detergent. Avoid bleach, chloride-based cleaners, steel wool and other aggressive or abrasive cleaning products that may cause staining or damage to the stainless steel surface.

For full care instructions, see our Stainless Steel Cleaning Guide.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**