

Cosmetal Floor Standing Chilled Drinking & Bottle Filling Fountain



Product Code: AAF-RIVERUP-FS

Cosmetal Floor Standing Chilled Drinking & Bottle Filling Fountain

Product Code: RIVERUP-FS

This modern and efficient Cosmetal River water fountain comes equipped with both a 23cm swan neck tap and a bubbler, providing flexible hydration options for users. Delivering up to 30 litres of chilled water per hour, it's more than capable of handling busy environments with high demand.

Built with user convenience in mind, this high-quality unit offers a smart and reliable hydration solution that adds a professional touch to any setting. For a cleaner, more secure setup, pair it with the compatible Cosmetal cowl to create a sleek and hygienic water station whilst adhering to BREEAM requirements for wall and floor fixing.

- Chrome plated drinking water bubbler tap and bottle filling tap.
- Floor standing.
- Connected directly to the mains water supply.
- Constructed using 1.2mm thick 304 grade stainless steel for durability.
- Requires a standard 240V electrical connection.
- Fitted with a UK 3-pin plug.
- Capable of delivering up to 30 litres of chilled water per hour.
- Features a satin stainless steel finish for a sleek appearance.
- Suitable for a wide range of settings, including educational environments.
- Requires a minimum mains water pressure of 2 bar.
- 24mm drainage pipe to connect to mains drainage.
- NSF REG4 Approved. Certificate number 2508059 valid until August 2030. (Equivalent to WRAS approval).
- CE certified for safety and compliance.
- Ice bank technology to help reduce costs.
- Intended for indoor use only.
- The water cooler is supplied with floor-standing feet and has no floor fixing points. Where additional security is required, an optional rear cowl is available, providing secure wall fixing, concealing pipework, and supporting compliance with BREEAM requirements.
- For ease of installation, an optional installation rail is available that includes the most commonly used components for connection to the mains water supply.
- **The items listed are supplied strictly on a return-to-base basis, with all repairs and warranty work to be carried out at the distributor's premises.**

Size

- 960mm High.
- 330mm Wide.
- 330mm Front to back.

Delivery

- From stock, usually 2 to 3 working days.

Optional Extras

- [Installation rail](#) with all necessary components, including a non-return valve, copper pressure-reducing valve, water block, and a replaceable filter (recommended filter change every 6 months).
- [Rear floor and wall mounting cowl](#) to securely fix the unit to the back wall and conceal pipework. Complies with BREEAM guidelines.

[Click here to see our full range of drinking fountains.](#)

****All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement. All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.****