

Wash Trough With Temposoft 2 Soft Touch Taps



Product Code: TSWT

Stainless Steel Wash Troughs With Delabie Temposoft Soft Touch Taps Bundle

Product Code TSWT

Upgrade your washroom with our high-quality stainless steel wash troughs, supplied complete with [Delabie Temposoft 2 soft-touch timed-flow taps](#). Designed for durability, hygiene, and water-saving performance, these trough sinks offer a dependable solution for high-traffic environments such as schools, leisure centres, workshops, and public washrooms.

Manufactured from 1.2mm thick 304 grade stainless steel, each wash trough is designed for long-term reliability and easy cleaning. Available in 1200mm, 1500mm, 1800mm, and 2400mm lengths, all models come with a 370mm projection, central 38mm waste outlet, and 2, 3 or 4 Delabie Temposoft 2 soft touch taps. Fast UK delivery ensures minimal downtime during installation. 370mm projection wash trough is ideal to minimise space used and helps children reach the taps.

Included Delabie Temposoft 2 Tap Configuration

The wash troughs are supplied complete with [Delabie Temposoft 2 soft-touch taps](#), providing exceptional ease of use and water efficiency.

Tap quantities per trough size:

- 1200mm wash trough – 2 Temposoft 2 taps
- 1500mm wash trough – 3 Temposoft 2 taps
- 1800mm wash trough – 3 Temposoft 2 taps
- 2400mm wash trough – 4 Temposoft 2 taps

Benefits of Delabie Temposoft 2 Soft-Touch Taps

Delabie Temposoft 2 soft-touch taps provide a smooth, effortless operation with a 7-second timed flow that can reduce water consumption by up to 85%. Designed to require around half the force of standard push-button taps, they are particularly well suited to schools, accessible washrooms, and environments with younger or less able users. Their user-friendly activation makes handwashing easier, safer, and more inclusive for everyone, while the timed shutoff ensures consistent water savings and improved hygiene in any washroom setting.

- Soft-touch activation suitable for children, accessible washrooms and all users.
- 7 second timed-flow shutoff prevents water waste and taps being left running.
- Flow rate is factory-set at 3 l/min (at 3 bar), but is fully adjustable between 1.4 and 6 l/min.
- Tamper-proof, scale-resistant flow straightener.
- Vandal-resistant chrome plated brass construction, ideal for busy public spaces.
- 1/2" connection with plastic back nut.
- Improved hygiene thanks to automatic shutoff.
- 30 year manufacturer's warranty.
- High durability and consistent performance in demanding environments.

These features make the Temposoft 2 taps a smart choice for schools and commercial washrooms, prioritising safety, hygiene, and reduced water consumption.

Key Product Features

- One-piece construction from 1.2mm 304 stainless steel.
- Four sizes available from stock for quick delivery.

- User capacity:
 - 1200mm – 2 users
 - 1500mm – 3 users
 - 1800mm – 3 users
 - 2400mm – 4 users
- Tap holes drilled to customer specification.
- 38mm central waste outlet.
- Integral wall fixing brackets for simple installation.
- Optional 600mm or 950mm front support legs.

Dimensions

- Length: 1200mm, 1500mm, 1800mm, 2400mm.
- Projection: 370mm front to back.
- Depth: 150mm with 25mm upstand.

Delivery

- In stock.
- Delivered in 1–2 working days across the UK.

Optional Extras

- [Stainless steel front support legs \(pair\)](#)
- [38mm plastic bottle trap](#)
- [Chrome-plated brass bottle trap with chrome waste pipe & flange](#)
- [Stainless steel wall or deck mounted soap dispensers](#)
- [Stainless steel paper towel dispensers](#)

All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement. All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.