Washware Essentials
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.washwareessentials.co.uk
Email: enquiries@washwareessentials.co.uk

316 Grade Wall Mounted Bottle Filler (Non-Chilled)



Product Code: 316-WMBF

316 Grade Stainless Steel Wall-Mounted Bottle Filling Station with Hand / Forearm Operated Water Supply

Product Code 316-WMBF

This durable, wall-mounted bottle filling station is manufactured from 316-grade stainless steel, known for its superior corrosion resistance, making it ideal for use in saltwater environments or areas with high humidity. Its surface-mounted design enables easy installation onto the face of a wall, with water supply and waste connections routed through the back wall. The vandal-resistant, compact design makes it suitable for installation in public spaces, ensuring a reliable bottle filling solution.

Key Features:

- Constructed from 316-grade stainless steel for enhanced corrosion resistance, especially in saltwater or coastal environments.
- **This unit does not have a built-in chilling system and will dispense water at the incoming mains water temperature, remote chillers are available.**
- Easy operation with hand or forearm, offering touch-free access to water.
- On/Off operation to help minimize water waste.
- Refilling plastic bottles reduces the reliance on single-use plastic, contributing to sustainability efforts.
- 1.2mm thick stainless steel for a robust and long-lasting build.
- 85mm space-saving projection – compact yet efficient design.
- Large bottle filling aperture to accommodate most drinking water bottles (up to 750ml).
- **KIWA REG4** approved product (see below for more information).
- Press button on / off filling valve.
- Keyhole slots for straightforward and hassle-free installation.
- Supplied with a 32mm waste fitting and flexible waste pipe for easy setup.
- To ensure the proper functioning and longevity of this unit, a Y-strainer or filter must be installed as part of the water supply system. The Y-strainer / filter is essential for protecting the internal components and maintaining the correct flow characteristics of the tap. Failure to install a Y-strainer or filter will result in the warranty being void.

Overall Dimensions

- Height: 545mm.
- Width: 350mm.
- Front to back: 85mm.

Bottle Aperture

- Height: 335mm.
- Width: 125mm.

Delivery

- From stock usually 1 to 2 working days.

Extras

- Y Strainer
- Inline water filter

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**