Washware Essentials
5 Brearley Court, Baird Road Waterwells Business Park Gloucester GL2 2AF
Phone: 01275 400456
Web: https://www.washwareessentials.co.uk
Email: enquiries@washwareessentials.co.uk

Blue Dry Eco Hand Dryer





Product Code: BIO-BDRY

Blue Dry Eco Hand Dryer

Product Code B-BDRY

The BlueDry Eco high-speed hand dryer combines powerful performance with energy-efficient operation. Designed with a durable grade 304 stainless steel body, this modern wall-mounted dryer delivers rapid hand drying in just 8–10 seconds. Its touch-free infrared sensor, high-speed motor and optional heater help reduce energy consumption while maintaining excellent drying performance. Available in polished stainless steel, brushed stainless steel, or white-coated stainless steel, it also features blue LED guide lights to ensure correct hand placement for optimal airflow.

- Constructed from durable grade 304 stainless steel with a polished finish, brushed stainless steel or white-coated stainless steel.
- Fast drying time of approximately 8–10 seconds.
- Cool blue LED guide lights show users the correct hand position for optimal airflow.
- Selectable heater element can be switched on or off to help reduce energy consumption and running costs.
- Smooth, seam-free casing provides a strong, vandal-resistant design.
- Wall-mounted unit for convenient installation.
- Touch-free infrared sensor operation ensures hygienic use.
- Power rating: 1800W with heater enabled, 550W with heater disabled.
- High-speed motor (25,000 RPM) delivers airflow up to 223 MPH.
- Supplied with a Blue Dry warranty – 2 years parts and 1 year labour.

Size

- 290mm wide.
- 170mm front to back.
- 320mm high.

Technical Specification

- Power supply: 220–240V AC / 50 Hz
- Output air temperature: Around 45°C at a 10 cm distance (based on 25°C ambient temperature)
- Maximum air velocity: 60 metres per second
- Air delivery rate: 140 cubic metres per hour
- Typical hand drying time: 8–10 seconds
- Sensor activation distance: Between 5 cm and 15 cm
- Water protection rating: IPX1
- Electrical protection: Class I isolation
- Weight (net): 4.4 kg
- Operational sound level: 74 dB at 1 m distance

Delivery

- From stock usually 1 to 3 working days.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not

fitting third party components.**