

1600mm Combined Sluice Sink (Slop Hopper) with Sink Bowl & Drainer – Right-Hand Sluice



Product Code: H-DUHS-16-RH

1600mm Combined Sluice Sink (Slop Hopper) with Sink Bowl & Drainer – Right-Hand Sluice

Washware Product Code: H-DUHS-16-RH

HBN designation: DUHS

The H-DUHS-16-RH is our current-generation 1600mm stainless steel DUHS combined sluice unit, featuring a right-hand sluice disposal bowl, central sink bowl and left-hand drainer/work surface within one wall-mounted unit.

Designed for hospitals, care homes, nursing homes and other healthcare environments, this combined DUHS unit provides a practical solution for sluice rooms and dirty utility rooms where a flushing disposal unit, separate sink bowl and additional working/draining space are required within a single stainless steel workstation.

Manufactured from high-quality Grade 304 stainless steel, the H-DUHS features a pressed worktop design that minimises joints and welds, providing durable, easy-to-clean surfaces for demanding healthcare environments. The current H-DUHS design also incorporates our improved flush pipe connection arrangement for easier installation.

Manufactured to meet the relevant requirements of HBN 00-10 Part C: Sanitary Assemblies, which superseded the former HTM 64 guidance.

Standard H-DUHS configurations are held in UK stock for fast delivery, typically within 1–2 working days.

What Is a DUHS Sluice Sink?

A DUHS is a combined wall-mounted sluice unit incorporating a sluice disposal bowl, separate sink bowl and drainer/work surface within a single stainless steel unit.

Measuring 1600mm wide x 600mm deep, the H-DUHS provides a complete working area for healthcare sluice and dirty utility rooms where more functionality is required than provided by a compact DU or DUH unit.

Two handed configurations are available:

H-DUHS-16-RH: right-hand sluice, centre sink bowl and left-hand drainer

[H-DUHS-16-LH: left-hand sluice, centre sink bowl and right-hand drainer](#)

This page is for the right-hand sluice configuration.

Key Features

- Current-generation H-DUHS combined sluice sink, sink bowl and drainer.
- HBN designation: DUHS.
- Right-hand sluice disposal bowl.
- Centrally positioned stainless steel sink bowl.
- Left-hand drainer/work surface.
- Overall dimensions: 1600mm x 600mm.
- Manufactured from high-quality Grade 304 stainless steel.
- Durable satin polished finish.
- Pressed stainless steel worktop designed to minimise joints and welds.

- Designed in accordance with relevant HBN 00-10 Part C sanitary assembly requirements.
- Full flushing rim to the sluice disposal bowl.
- Anti-drip front edge with folded safety edges.
- Heavy-duty wall mounting brackets supplied.
- Optional stainless steel front support legs.
- Choice of top entry or back entry flush pipe connection.
- Top entry version supplied with a 500mm stainless steel flush pipe.
- Plain spigot sluice outlet 110mm.
- Optional polypropylene P trap or S trap.
- Held in UK stock for fast 1–2 working day delivery.

Right-Hand or Left-Hand DUHS?

The handing of a DUHS describes the position of the sluice disposal bowl when the unit is viewed from the front.

Right-Hand Sluice – H-DUHS-16-RH

This model has the sluice disposal bowl on the right, a separate sink bowl in the centre and the drainer/work surface on the left.

[Left-Hand Sluice – H-DUHS-16-LH](#)

The corresponding left-hand model has the sluice disposal bowl on the left, a separate sink bowl in the centre and the drainer/work surface on the right.

Select the handing that best suits the room layout, position of existing services and required working arrangement.

Sluice Disposal Bowl

The right-hand sluice bowl provides a dedicated flushing disposal point for the hygienic disposal of appropriate body waste and the contents of items such as bedpans, urine bottles and vomit bowls.

Features include:

- Full flushing rim for effective and even flushing.
- Plain spigot waste outlet 100mm.
- Optional polypropylene P trap or S trap.
- Choice of top entry or back entry flush connection.

Top Entry

Choose Top Entry where the flushing cistern will be exposed and surface mounted on the wall above the sluice unit.

Top entry models are supplied with a 500mm stainless steel flush pipe.

Back Entry

Choose Back Entry where the flushing cistern will be concealed within a service duct or behind the wall.

The flush connection enters the sluice bowl from behind, allowing the cistern and associated pipework to remain concealed.

Centre Sink Bowl

The H-DUHS incorporates a separate Grade 304 stainless steel sink bowl in the centre of the unit.

Bowl dimensions: 500mm x 400mm x 200mm.

Waste: 38mm unslotted flush grated waste.

Overflow: None.

Tap holes: None as standard.

Optional tap-hole configurations include:

- One central tap hole.
- Two tap holes.

Available tap-hole sizes:

- 22mm.
- 30mm.
- 35mm.

The required tap arrangement should be selected to suit the intended use and specified tapware.

Cistern Options

The H-DUHS-16-RH can be supplied with a choice of flushing cisterns to suit exposed or concealed installations:

- Stainless steel exposed manual cistern with front operating lever.
- Plastic exposed cistern complete with flush pipe and front operating lever.
- Plastic concealed cistern complete with flush pipe and through-wall operating lever.

Concealed Cistern Dimensions

Width: 505mm

Height: 285mm

Depth: 146mm

Exposed Cistern Dimensions

Width: 455mm

Height: 318mm

Depth: 155mm

DU, DUH or DUHS – Which Do I Need?

The HBN designation identifies the configuration of the sluice unit:

[DU – compact wall-mounted sluice disposal unit.](#)

[DUH – sluice disposal unit with additional drainer/work surface.](#)

DUHS – combined sluice disposal unit with a separate sink bowl and drainer/work surface.

Choose a DUHS where a sluice disposal bowl, separate sink and additional working/draining space are required within one integrated stainless steel unit.

Product Dimensions & Specification

- Overall width: 1600mm.
- Overall depth: 600mm.
- Configuration: Right-hand sluice / centre sink / left-hand drainer.
- Material: Grade 304 stainless steel.
- Finish: Satin polished.
- Sluice outlet: 110mm plain spigot.
- Sink bowl: 500mm x 400mm x 200mm.
- Sink waste: 38mm unslotted flush grated waste.
- Flush connection: Top entry or back entry.
- HBN designation: DUHS.
- Washware product code: H-DUHS-16-RH.
- [Download our explanation guide to sluice sinks here.](#)

Where Is a DUHS Combined Sluice Unit Used?

The H-DUHS is designed primarily for healthcare sluice rooms and dirty utility rooms requiring a combined disposal, sink and working/draining area.

Typical applications include:

- NHS hospitals.
- Private hospitals.
- Care homes.
- Nursing homes.
- Hospices.
- Healthcare facilities.
- Sluice rooms.
- Dirty utility rooms.

Delivery

Standard H-DUHS right-hand sluice configurations, including top- and back-entry variants, are held in UK stock for fast delivery, typically within 1–2 working days.

The unit is delivered securely on a pallet to help protect the stainless steel equipment during transport.

Need the Opposite Hand?

If your room layout requires the sluice disposal bowl on the left-hand side, select the [H-DUHS-16-LH left-hand sluice model](#), which provides a left-hand sluice, central sink bowl and right-hand drainer.

If you are unsure which handing, flush connection, cistern or waste arrangement is required, contact the Washware Essentials team for specialist product and technical advice. [Read our Sluice Sink Guide for DU, DUH and DUHS models, top/back entry, handing, cisterns and waste connections.](#)

****All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.
All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.****